



# Technical Data Sheet

A64-043  
Double Coated Rubber Adhesive

## Specifications

**Double Coated Tape with a general purpose, high tack, high peel adhesive.  
Provided on 60# densified Kraft release liner.**

**Designed for excellent adhesion to urethane foams, low density sponge rubber and polyethylene foams..**

**Liner side adhesive provides excellent adhesion to metal, ABS, polypropylene, and other low surface energy materials.**

## Physical Properties

Physical Property	Test Method	Unit	Value
Thickness: Liner Side Adhesive	PSTC-33 / ASTM D3652	Mils	1.1
Thickness: Carrier	PSTC-33 / ASTM D3652	Mils	.05
Peel Adhesion	PSTC-101 / ASTM D3330	OZ Force/In Width	85
Elevated Temperature Test	ASTM D4498 (Modified)		155° F

Surface Preparation: All surfaces should be clean, dry, and free of grease, dirt and other contaminants.

Shelf Life: 12 Months when stored at 72° F and 50% relative humidity, out of direct sunlight.

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.