

## Description

- Closed-Cell foam which bonds using surface energy rather than adhesive
- Provides residue free release from glass, ceramic finishes, metal and plastics
- Can be combined with cork composition, chemically cross-linked polyethylene foam or other materials to be used as shipping pads

## Physical Properties

Physical Property	Test Method	Unit	Value
Color			Natural
Density	ASTM D-1667	PCF	11 +/-4
Compression Deflection	ASTM D-1667	PSI	5.0
Hardness	ASTM D-2240	Shore 00	45
Water Absorption	ASTM D-1056	%	3
Tensile Strength	ASTM D-412 (Die A)	PSI	50
Thickness		IN	.06
Maximum Service Temperature		°F	172
Minimum Service Temperature		°F	-4

Surface Preparation: Surface to which the tape is applied must be clean, dry and free of grease and oil.

Storage and Shelf Life: Six months when stored at or below 75°F and 50% relative humidity, out of direct light.

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.