

## Specifications

- 8# PVC Foam is a light density, closed-cell foam. This economical, general purpose foam tape is used in Applications requiring positive seals on irregular surfaces or when flex and conformity to seal tight radius curves are critical considerations.
- Characteristics of 8# PVC Foam include the ability to make a long life sea against air, moisture, light and dust when compressed 30% or more.
- Absorbs shocks, cushions, deadens sound and eliminates excess vibration.
- Inherently resistant to fire, ultraviolet rays, most chemicals, acids and solvents.

## Physical Properties

Physical Property	Test Method	Unit	Value
Density	ASTM D-1667	LBS/FT <sup>3</sup>	8
Hardness	ASTM D-2240	Shore 00	25
Compression Deflection @ 25%	ASTM D-1667	PSI	2
Compression Set @ 25%	ASTM D-1667	%	4
Water Absorption (% by Volume)	GTP(1)	%	1.0
Tensile Strength	ASTM D-412	PSI	30
Percent Elongation	ASTM D-415	%	150
Thermal Conductivity	ASTM C-518	K factor	0.27
Recommended Service Temp.		° F	-40 to 180
Recommended Application Temp.		° F	50 to 110
Fungi Resistance			Excellent
Oxidation Resistance			Excellent
Weather Resistance			Excellent
Color			Grey

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.