

Specifications

- **Double-Coated Foam Tape System:** closed cell, cross-linked polyethylene foam coated on both sides with an all acrylic adhesive
- **UV and water resistant**
- **Foam carrier provides gap filling for bonding to irregular surfaces**
- **Seals against air, moisture, light and dust**
- **Provides cushioning to absorb vibration and shock**
- **Thermal insulating and sound deadening**
- **Available in 1/32", 1/16" and 1/8" thicknesses**

Physical Properties

| Physical Property | Test Method | Unit | Value |
|-------------------------------|---------------------|--------------|-----------------|
| Air-side Adhesive Thickness | PSTC 133 | Mils | 2.0 |
| Liner-side Adhesive Thickness | PSTC 133 | Mils | 2.0 |
| Peel Adhesion | PSTC 101 | PIW | 12.2 |
| Shear Strength | PSTC 107 (modified) | Days to Fail | >7 |
| Service Temperature | | °F | -30 to 220 |
| Application Temperature | | °F | 68 to 100 |
| Color | | | White and Black |

Surfaces to be bonded to should be clean, dry, and free from grease and oil.

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.