



Technical Data Sheet

SM Series SureMount Foam Tape

Specifications

- **Double-Coated Foam Tape System:** closed cell, cross-linked polyethylene foam coated on both sides with a synthetic rubber adhesive.
- For use in mounting signs, wire clips, moldings, reflectors, molded and extruded plastics, hardware, etc.
- Moderate tack and excellent shear and adhesion to most surfaces
- Foam carrier provides gap filling for bonding to irregular surfaces
- Closed cell foam does not absorb water
- Available in 1/32", 1/16" and 1/8" thicknesses

Physical Properties

Physical Property	Test Method	Unit	Value
Peel Adhesion	PSTC 101	Oz/in	160
Shear Adhesion: Air Side	PSTC 107 (modified)	Days to Fail	14+ No creep
Shear Adhesion: Liner Side	PSTC 107 (modified)	Days to Fail	14+ No creep
Service Temperature		°F	30 to 150
Application Temperature		°F	68 to 100
Color			White

Surfaces should be dry, clean and free from grease and oil. These products should not be laminated to any material that contains migrating plasticizers.

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.